

Offer valid until 31.03.2024

## Oxygen analyser<br/>Oxy HP 2.0 with documentation

Item no. 8025



- Simple menu navigation
- · LED display, parameter entry by membrane keyboard
- · Temperature-controlled zirconium sensor
- Measuring cell made of zirconium oxide (maintenancefree), long service life due to intelligent cell management
- Measuring range 5 999 ppm O2
- Suitable for inert gases and gases with hydrogen content of max. 10 %
- Battery-powered oxygen analyser with an operating time of up to 8 hours
- Wall wart 110 VAC 240 VAC, supply voltage 12 V
- USB interface for storage of parameter sets
- Documentation of residual oxygen value, date, time and name of project
- Different interfaces, USB, 0 5 VDC, digital
- Freely adjustable operating range
- · Language selection German and English
- · Memory of the validation process
- Visual signal during the measurement when the measuring value is not achieved yet
- Robust plastic case with protective rubber frame, external dimensions (L x W x H) 185 x 93 x 36 mm, weight 450 g
- Tube set 1 m, including filter and stainless steel probe
- Validation certificate
- Including transport case

**Special offer price** 

1.450.00 Euro

plus VAT, ex works

Hotline: +49 (0) 261 98 88 380-0



Visit our website: www.owt-orbital.com

OWT GmbH & Co. KG | Postfach 100306 | D-56033 Koblenz | Delivery address: In der Florinskaul 13 | D-56218 Mülheim-Kärlich Tel.: +49 (0) 261 98 88 380-0 | Fax: +49 (0) 261 98 88 380-9 | Mobile: +49 (0) 172 8304731 | E-Mail: info@owt-orbital.com